



CLOVER CHEMICALS



FLOORCARE RANGE

AREA OF USE	FOR USE ON	PRODUCT DILUTION	PRODUCT USAGE	HEALTH & SAFETY	HANDY TIPS
	POLISHED FLOORS, MARBLE, TERRAZZO, ANTI-SLIP/ TEXTURED FLOORS, AND ALL WATER WASHABLE HARD SURFACES	SPiRiT LIGHT SOIL 50-1	FRAGRANT MULTI-SURFACE CLEANER SPiRiT MAY BE DILUTED WITH HOT OR COLD WATER. USE THE SOLUTION OF SPiRiT WITH A MOP, SPONGE, CLOTH OR TRIGGER SPRAY. SPiRiT LEAVES AN ENHANCING SATIN FINISH WHEN DRY.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	CLEANS & FRESHENS IN ONE OPERATION. SAFE FOR USE ON MOST WATER WASHABLE HARD SURFACES. THE IDEAL PRODUCT FOR TIME SENSITIVE CLEANING JOBS.
	A NON-FRAGRANCED PRODUCT IDEAL FOR CLEANING HARD FLOOR SURFACES	MPC LIGHT SOIL 40-1	MULTI-PURPOSE CLEANER MPC MAY BE DILUTED WITH HOT OR COLD WATER. USE THE SOLUTION OF MPC WITH A MOP, SPONGE OR CLOTH. RINSE AWAY WITH CLEAN WATER.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	FOR THE EFFECTIVE CLEANING OF LARGE FLOOR AREAS USE THROUGH A SCRUBBER DRIER AT A DILUTION OF 1 PART MPC TO 30 PARTS OF WATER.
 pH7 FINISH	POLISHED LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD AND TERRAZZO	ZIP STRIP DILUTE 10-1	RINSE FREE FLOOR POLISH STRIPPER STRIPS METALISED POLISH FROM FLOORS. DILUTE WITH WATER AND MOP OVER THE FLOOR. AFTER 10-15 MINUTES THE FLOOR POLISH WILL TURN WHITE, SCRUB ALL WHITE FILM FROM THE FLOOR AND RINSE WITH WATER.	 IRRITANT IRRITATING TO EYES AND SKIN. KEEP OUT OF THE REACH OF CHILDREN. IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE. DO NOT BREATHE SPRAY.	ZIP STRIP CAN DARKEN WOODEN FLOORS AND LINOLEUM. ALWAYS CHECK THE COLOUR FASTNESS OF THE SURFACE BEFORE USE.
 pH7 FINISH	POLISHED LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD AND TERRAZZO	UB90 <i>ULTRABLEND 4</i>	RINSE FREE FLOOR POLISH STRIPPER CONCENTRATE STRIPS METALISED POLISH FROM FLOORS. DILUTE WITH WATER AND MOP OVER FLOOR. AFTER 10-15 MINUTES THE FLOOR POLISH WILL TURN WHITE, SCRUB ALL WHITE FILM FROM THE FLOOR AND RINSE WITH WATER.	 HARMFUL HARMFUL BY INHALATION. IRRITATING TO EYES, RESPIRATORY SYSTEM AND SKIN. KEEP OUT OF THE REACH OF CHILDREN. IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE. DO NOT BREATHE SPRAY.	ONLY USE UB90 STRIPPER THROUGH CLOVER'S <i>ULTRABLEND 4</i> DOSING SYSTEM. UB90 CAN DARKEN WOODEN FLOORS AND LINOLEUM. ALWAYS CHECK THE COLOUR FASTNESS OF THE SURFACE BEFORE USE.
	POLISHED LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD AND TERRAZZO	REMOVE DILUTE 10-1	FLOOR POLISH STRIPPER STRIPS EMULSION POLISH FROM FLOORS. DILUTE WITH WATER AND MOP OVER FLOOR. AFTER 10-15 MINUTES THE FLOOR POLISH WILL TURN WHITE, SCRUB ALL WHITE FILM FROM THE FLOOR AND RINSE WITH WATER.	 IRRITANT CONTAINS 0.8 % SODIUM HYDROXIDE IRRITATING TO EYES AND SKIN KEEP OUT OF REACH OF CHILDREN	REMOVE CAN BE USED UNDILUTED FOR A HEAVY BUILD UP OF POLISH. USE A FINAL RINSE OF VINEGAR AND WATER TO ENSURE THE FLOOR IS pH NEUTRAL BEFORE APPLYING POLISH.
	CLEANS CARPET, UPHOLSTERY AND FABRICS. IDEAL FOR USE THROUGH SPRAY EXTRACTION EQUIPMENT	COMET DILUTABLE	EXTRACTION CLEANER DETERGENT ADD A SOLUTION TO THE DETERGENT TANK, 1-40 FOR HEAVY DUTY CLEANING, 1-80 FOR NORMAL CLEANING. CLEAN THE CARPET TAKING CARE TO EXTRACT AS MUCH LIQUID AS POSSIBLE. ALLOW TO DRY.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	VACUUM BEFORE CLEANING. ALWAYS TEST THE FABRIC FOR RESISTANCE TO THE CLEANING SOLUTION. EXTRACT AS MUCH LIQUID AS POSSIBLE.
	CLEANS CARPET, UPHOLSTERY AND FABRICS. IDEAL FOR USE THROUGH SPRAY EXTRACTION EQUIPMENT	ORBIT DILUTABLE	EXTRACTION CLEANER ADDITIVE ADD A SOLUTION TO THE DETERGENT TANK, 1-50 FOR HEAVY DUTY CLEANING, 1-100 FOR NORMAL CLEANING. CLEAN THE CARPET TAKING CARE TO EXTRACT AS MUCH LIQUID AS POSSIBLE. ALLOW TO DRY.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	VACUUM BEFORE CLEANING. ALWAYS TEST THE FABRIC FOR RESISTANCE TO THE CLEANING SOLUTION. EXTRACT AS MUCH LIQUID AS POSSIBLE.
	FOR CLEANING CARPETS WITH BRUSH OPERATED CARPET CLEANING MACHINES. MINIMISES WETTING TO REDUCE DRYING TIME	DRY FOAM DILUTE 15-1	DRY FOAM CARPET SHAMPOO DILUTE 1 PART DRY FOAM WITH 15 PARTS OF WARM WATER. APPLY THE SOLUTION SPARINGLY, WORKING UP A GOOD DEGREE OF LATHER WITH THE BRUSH. LEAVE THE CARPET TO DRY AND THEN VACUUM AWAY LOOSE DIRT.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	VACUUM BEFORE CLEANING. ALWAYS TEST THE FABRIC FOR RESISTANCE TO THE CLEANING SOLUTION. EXTRACT AS MUCH LIQUID AS POSSIBLE.
	CLEANS WATER WASHABLE CARPETS, FABRICS AND UPHOLSTERY	SAS 20 UNDILUTED	SPOT & STAIN REMOVER SPRAY ONTO SPOT WETTING THE WHOLE AREA, WIPE OR BLOT AND ALLOW TO DRY. VACUUM OR BRUSH AWAY. FOR USE ON GREASY MARKS AND GENERAL SOILING.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	WORK INTO STAIN USING A SOFT BRUSH. USE A CLEAN CLOTH OR LINT FREE PAPER TO ABSORB DIRT.
	ONLY USE ON SOLVENT RESISTANT SURFACES AND FABRICS WITH A SOLVENT RESISTANT BACKING	DETAk UNDILUTED	CHEWING GUM REMOVER DAB OR POUR ONTO THE GUM. ALLOW A SHORT TIME TO ACTIVATE AND SCRAPE THE GUM AWAY. ALWAYS CHECK THE CARPET TYPE BEFORE CLEANING. CONSULT MSDS SHEET FOR DIRECTIONS.	 HARMFUL DANGEROUS FOR THE ENVIRONMENT FLAMMABLE - IRRITATING TO SKIN. HARMFUL - MAY CAUSE LUNG DAMAGE IF SWALLOWED. REPEATED EXPOSURE MAY CAUSE SKIN DRYNESS OR CRACKING. TOXIC TO AQUATIC ORGANISMS. MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. KEEP OUT OF THE REACH OF CHILDREN. DO NOT BREATHE SPRAY. IN CASE OF CONTACT WITH EYES, RINSE IMMEDIATELY WITH PLENTY OF WATER AND SEEK MEDICAL ADVICE. AVOID RELEASE TO THE ENVIRONMENT. REFER TO SPECIAL INSTRUCTIONS/SAFETY DATA SHEETS.	ENSURE DETAK COVERS THE AREA AROUND THE GUM THOROUGHLY TO PREVENT RE-ADHESION OF THE GUM.



CLOVER CHEMICALS



FLOORCARE RANGE

AREA OF USE	FOR USE ON	PRODUCT DILUTION	PRODUCT USAGE	HEALTH & SAFETY	HANDY TIPS
	LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD, SEALED CORK, TERRAZZO AND MARBLE	DIAMOND CONTRACT UNDILUTED	DRY BRIGHT FLOOR POLISH DIAMOND CONTRACT POLISHES AND PROTECTS FLOORING. DIAMOND CONTRACT PROVIDES A PERFECT BASE FOR CLEANING AND MAINTAINING USING A SPRAY BURNISHING TECHNIQUE.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	ALWAYS USE A CLEAN MOP OR APPLICATOR AND APPLY AT LEAST 2 COATS. LEAVE A SUITABLE DRYING TIME BETWEEN COATS. TYPICAL COVERAGE 300m ² /5LTR.
	LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD, SEALED CORK, TERRAZZO AND MARBLE	DIAMOND UNDILUTED	SUPER HIGH SOLIDS DRY BRIGHT FLOOR POLISH DIAMOND POLISHES AND PROTECTS FLOORING. DIAMOND PROVIDES A PERFECT BASE FOR CLEANING AND MAINTAINING USING A SPRAY BURNISHING TECHNIQUE.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	ALWAYS USE A CLEAN MOP OR APPLICATOR AND APPLY AT LEAST 2 COATS. LEAVE A SUITABLE DRYING TIME BETWEEN COATS. TYPICAL COVERAGE 300m ² /5LTR.
	LINOLEUM, VINYL, THERMOPLASTIC, SEALED CORK AND TERRAZZO	DIAMOND EXTRA UNDILUTED	WET LOOK FLOOR POLISH PROTECTS FLOORS AND CREATES A TOUGH SHINY FINISH THAT GETS TOUGHER AND SHINIER EACH TIME IT IS BUFFED.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	CONSULT MSDS SHEET TO ENSURE CORRECT PREPARATION AND METHOD OF USE. APPLY A MINIMUM OF 2 COATS FOR OPTIMUM RESULTS. TYPICAL COVERAGE 300m ² PER 5LTR.
	UNSEALED WOOD, VARNISHED WOOD, HARDWOOD PARQUET AND BLOCK FLOORS	CLEAR VARNISH UNDILUTED	ADVANCED CLEAR VARNISH IDEAL FOR TREATING UNSEALED HARDWOOD FLOORS. CREATES A TOUGH, HARD-WEARING GLOSS FINISH.	 Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains Cobalt Carboxylate. May produce an allergic reaction. Keep out of the reach of children. Wear suitable gloves. Use only in well-ventilated areas. DAANGEROUS FOR THE ENVIRONMENT	ALWAYS USE A CLEAN BRUSH OR APPLICATOR AND APPLY AT LEAST 2 COATS. LEAVE A SUITABLE DRYING TIME BETWEEN COATS. TYPICAL COVERAGE 12m ² /5LTR.
	CONCRETE, STONE AND STEEL	GREY FLOOR SEAL RED FLOOR SEAL UNDILUTED	ADVANCED FLOOR SEAL PROTECTS FLOORS AND CREATES A TOUGH POLYMER FINISH. IDEAL FOR USE IN GARAGES, SHOWROOMS, FACTORIES, WAREHOUSES, SCHOOLS, HOSPITALS AND PUBLIC BUILDINGS.	 Flammable. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Contains Cobalt Carboxylate. May produce an allergic reaction. Keep out of the reach of children. Wear suitable gloves. Use only in well-ventilated areas. DAANGEROUS FOR THE ENVIRONMENT	USE ACID WASH 80 TO CLEAN AND ETCH CONCRETE FLOORS PRIOR TO TREATMENT TO ENSURE GOOD ADHESION AND THE MAXIMUM LIFE SPAN OF THE FLOOR PAINT.
	LINOLEUM, VINYL, THERMOPLASTIC, SEALED WOOD, SEALED CORK AND TERRAZZO	P.D.Q. DILUTE 15-1	POLYMERIC WAX FLOOR MAINTAINER MAINTAIN EMULSION POLISH BY SPRAY BURNISHING AT 1 PART P.D.Q. TO 8 PARTS CLEAN WATER TO CREATE A SLIP RESISTANT GLOSS FINISH.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	SWEEP THE FLOOR FIRST. APPLY P.D.Q. BY EITHER DAMP MOPPING OR SPRAYING ONTO THE FLOOR AND BURNISHING TO A SLIP RESISTANT SHINE.
	LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD, SEALED CORK, TERRAZZO, QUARRY TILES AND MARBLE	RENEW TD DILUTE 20-1	POLYMER FLOOR MAINTAINER MAINTAIN EMULSION POLISH BY EITHER DAMP MOPPING 1 PART RENEW TD TO 20 PARTS CLEAN WATER OR SPRAY BURNISHING AT 1 PART RENEW TD TO 10 PARTS CLEAN WATER.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	SWEEP THE FLOOR TO REMOVE DUST BEFORE SPRAY BURNISHING. USE A SEPARATE MOP AND BUCKET FOR RENEW TD.
	LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD, SEALED CORK, TERRAZZO, QUARRY TILES AND MARBLE	UB60 <i>ULTRABLEND 4</i>	CONCENTRATED FLOOR MAINTAINER MOP THE SOLUTION ON TO THE FLOOR, AGITATE IF NECESSARY, REMOVE EXCESS LIQUID AND ALLOW TO DRY TO A SHEEN, OR BURNISH FOR AN IMPROVED GLOSS FINISH.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	UB60 FLOOR MAINTAINER SHOULD ONLY BE USED THROUGH CLOVER'S <i>ULTRABLEND 4</i> DOSING SYSTEM TO ENSURE OPTIMUM RESULTS.
	LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD, FLOORS, WALLS, SKIRTING BOARDS AND HARD SURFACES	IMPACT LIGHT SOIL 120-1	LEMON CLEANING GEL IMPACT MAY BE DILUTED WITH HOT OR COLD WATER. USE THE SOLUTION OF IMPACT WITH A MOP, SPONGE OR CLOTH. BURNISHING VINYL FLOORS GIVES A SLIP RESISTANT SHINE.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	WHERE POSSIBLE DILUTE WITH WARM WATER AND ENSURE THE CLEANING SOLUTION IS THOROUGHLY MIXED. FOR BEST RESULTS BURNISH AFTER DAMP MOPPING.
	LINOLEUM, VINYL, THERMOPLASTIC, RUBBER, SEALED WOOD, FLOORS, WALLS, SKIRTING BOARDS AND HARD SURFACES	CLOVER GEL LIGHT SOIL 120-1	BACTERICIDAL FLOOR GEL REGULAR/CONTRACT CLOVER GEL MAY BE DILUTED WITH HOT OR COLD WATER. USE THE SOLUTION OF CLOVER GEL WITH A MOP, SPONGE OR CLOTH. BURNISHING VINYL FLOORS GIVES A SLIP RESISTANT SHINE.	EYES - WASH OUT WITH PLENTY OF CLEAN WATER. SKIN - WIPE OFF OR WASH OFF WITH WATER. KEEP OUT OF REACH OF CHILDREN.	WHERE POSSIBLE DILUTE WITH WARM WATER AND ENSURE THE CLEANING SOLUTION IS THOROUGHLY MIXED. FOR BEST RESULTS BURNISH AFTER DAMP MOPPING.

HEALTH & SAFETY



WEAR RUBBER GLOVES



WEAR EYE/FACE PROTECTION

CLOVER CHEMICALS LTD, CLOVER HOUSE, MACCLESFIELD ROAD, WHALEY BRIDGE, HIGH PEAK SK23 7DQ
TEL: + 44 (0)1663 733114 FAX: + 44 (0)1663 733115
www.cloverchemicals.com